## NSN 5306-01-160-5691

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-160-5691 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.351 inches and 0.418 inches **Fastener Length:** Between 0.861 inches and 0.908 inches **Head Style:** Double hexagon **Head Height:** Between 0.154 inches and 0.174 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2483 inches and 0.2492 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 2 cl 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5306-01-160-5691

Shear Bolt - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.