# NSN 5306-01-161-2590

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-161-2590



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.400 inches and 0.450 inches

# Fastener Length:

Between 0.910 inches and 0.940 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.430 inches and 0.439 inches

#### **Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

#### **Thread Diameter:**

0.250 inches

# Grip Length:

Between 0.490 inches and 0.510 inches

## Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

160000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5306-01-161-2590

Shear Bolt - Page 2 of 2

Fiig: A003b0

