## NSN 5306-01-161-7278

Machine Bolt - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5306-01-161-7278



3a **Thread Direction: Right-hand Thread Length:** Between 0.757 inches and 0.797 inches Fastener Length: Between 0.865 inches and 0.885 inches Head Style: Double hexagon w/hole **Head Height:** Between 0.338 inches and 0.358 inches Width Between Flats: 0.375 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches **Thread Diameter:** 0.312 inches Grip Length: Between 0.088 inches and 0.108 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c **Minimum Yield Strength:** 85000 pounds per square inch Hole Configuration Style: Double hexagon longitudinal hole Surface Finish:

32.0 microinches threads

## NSN 5306-01-161-7278

Machine Bolt - Page 2 of 2



Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0