NSN 5306-01-161-7279

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-161-7279

Thread Direction: Right-hand Thread Length: Between 0.865 inches and 0.922 inches Fastener Length: Between 0.990 inches and 1.010 inches Head Style: Double hexagon w/hole Head Height: Between 0.338 inches and 0.358 inches Width Between Flats: 0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches Hole Quantity:
Right-hand Thread Length: Between 0.865 inches and 0.922 inches Fastener Length: Between 0.990 inches and 1.010 inches Head Style: Double hexagon w/hole Head Height: Between 0.338 inches and 0.358 inches Width Between Flats: 0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Thread Length: Between 0.865 inches and 0.922 inches Fastener Length: Between 0.990 inches and 1.010 inches Head Style: Double hexagon w/hole Head Height: Between 0.338 inches and 0.358 inches Width Between Flats: 0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Between 0.865 inches and 0.922 inches Fastener Length: Between 0.990 inches and 1.010 inches Head Style: Double hexagon w/hole Head Height: Between 0.338 inches and 0.358 inches Width Between Flats: 0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Fastener Length: Between 0.990 inches and 1.010 inches Head Style: Double hexagon w/hole Head Height: Between 0.338 inches and 0.358 inches Width Between Flats: 0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Between 0.990 inches and 1.010 inches Head Style: Double hexagon w/hole Head Height: Between 0.338 inches and 0.358 inches Width Between Flats: 0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Head Style: Double hexagon w/hole Head Height: Between 0.338 inches and 0.358 inches Width Between Flats: 0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Double hexagon w/hole Head Height: Between 0.338 inches and 0.358 inches Width Between Flats: 0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Head Height: Between 0.338 inches and 0.358 inches Width Between Flats: 0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Between 0.338 inches and 0.358 inches Width Between Flats: 0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Width Between Flats: 0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
0.375 inches Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Extended Washer Diameter: Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Between 0.490 inches and 0.510 inches Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Extended Washer Thickness: 0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
0.070 inches Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Hole Diameter: Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Between 0.060 inches and 0.080 inches Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Thread Diameter: 0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
0.312 inches Grip Length: Between 0.088 inches and 0.125 inches
Grip Length: Between 0.088 inches and 0.125 inches
Between 0.088 inches and 0.125 inches
Hole Quantity:
4
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
130000 pounds per square inch
Hardness Rating:
24.0 rockwell c and 35.0 rockwell c
Minimum Yield Strength:
85000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Surface Finish:
32.0 microinches threads

NSN 5306-01-161-7279

Machine Bolt - Page 2 of 2



Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0