

View Online at <https://aerobasegroup.com/nsn/5306-01-161-7281>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.500 inches

Fastener Length:

6.500 inches

Head Style:

Hexagon

Head Height:

0.403 inches

Width Between Flats:

0.938 inches

End Application:

Nsn 2320-01-097-0260 hemtt (heavy expanded mobility tactical truck); nsn 2320-01-304-2277 pls (palletized loading system)

Thread Diameter:

0.625 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

11

Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1524 or steel comp 1527 or steel comp 1536 or steel comp 1541

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-p-16232 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-p-16232 spec.