NSN 5306-01-161-7293



Externally Relieved Body Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-161-7293 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.785 inches **Fastener Length:** Between 3.615 inches and 3.635 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Hole Diameter:** Between 0.140 inches and 0.160 inches **First Diameter From Head:** Between 0.218 inches and 0.228 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 2.815 inches and 2.875 inches **Thread Diameter:** 0.250 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Double hexagon longitudinal hole **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** Ams7477 assn standard single material response

Surface Treatment:

Cadmium

NSN 5306-01-161-7293

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0