

View Online at <https://aerobasegroup.com/nsn/5306-01-161-7293>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.785 inches

**Fastener Length:**

Between 3.615 inches and 3.635 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.320 inches and 0.340 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**Hole Diameter:**

Between 0.140 inches and 0.160 inches

**First Diameter From Head:**

Between 0.218 inches and 0.228 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 2.815 inches and 2.875 inches

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Stainless steel

**Material Specification:**

Ams7477 assn standard single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0