

View Online at <https://aerobasegroup.com/nsn/5306-01-162-0017>

Threads Per Inch:

24 counterbore

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.395 inches and 0.505 inches

Fastener Length:

Between 0.495 inches and 0.505 inches

Head Style:

Hexagon

Head Height:

Between 0.370 inches and 0.380 inches

Width Between Flats:

Between 0.615 inches and 0.625 inches

Concentric Hole Diameter:

Between 0.174 inches and 0.180 inches

Internal Thread Length:

0.250 inches counterbore

Thread Diameter:

0.438 inches

Thread Series:

Uns counterbore

Internal Thread Direction:

Right-hand counterbore

Thready Qty Per Inch (tpi):

20

Thread Size:

0.438 inches counterbore

Internal Thread Class:

2b counterbore

Special Features:

Pac sftt is for stl matl only

Material:

Steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1212 or steel comp 1213

Material Specification:

Astm a108 assn standard all material responses

Surface Treatment:

Copper or tin

Surface Treatment Specification:

Mil-c-14550 cl 2 military specification 1st treatment response or mil-t-10727 type 1 military specification 2nd treatment response

Style Designator:

Counterbore threaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-14550 spec.