

View Online at <https://aerobasegroup.com/nsn/5306-01-162-3818>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.470 inches and 0.505 inches

**Fastener Length:**

Between 0.860 inches and 0.890 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.234 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.438 inches

**Extended Washer Thickness:**

0.069 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.365 inches and 0.386 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0