## NSN 5306-01-162-9697

Shear Bolt - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5306-01-162-9697 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.763 inches and 0.813 inches **Fastener Length:** Between 5.773 inches and 5.803 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.504 inches Width Between Flats: 0.562 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** 0.123 inches **Grip Diameter:** Between 0.5027 inches and 0.5039 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 4.990 inches and 5.010 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

## NSN 5306-01-162-9697

Shear Bolt - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0