

View Online at <https://aerobasegroup.com/nsn/5306-01-162-9702>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.763 inches and 0.813 inches

**Fastener Length:**

Between 5.523 inches and 5.553 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.504 inches

**Width Between Flats:**

0.562 inches

**Extended Washer Diameter:**

Between 0.818 inches and 0.828 inches

**Extended Washer Thickness:**

0.123 inches

**Grip Diameter:**

Between 0.5047 inches and 0.5059 inches

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 4.740 inches and 4.760 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0