## NSN 5306-01-162-9707

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-162-9707



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.763 inches and 0.813 inches

## Fastener Length:

Between 4.398 inches and 4.428 inches

#### Head Style:

Double hexagon w/hole

#### **Head Height:**

0.504 inches

#### Width Between Flats:

0.562 inches

#### **Extended Washer Diameter:**

Between 0.818 inches and 0.828 inches

#### **Extended Washer Thickness:**

0.123 inches

### **Grip Diameter:**

Between 0.5047 inches and 0.5059 inches

## **Thread Diameter:**

0.500 inches

## Grip Length:

Between 3.615 inches and 3.635 inches

#### Thready Qty Per Inch (tpi):

20

#### Min. Tensile Strength (psi):

180000 pounds per square inch

#### Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

#### Surface Finish:

32.0 microinches grip

#### Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5306-01-162-9707

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

