

View Online at <https://aerobasegroup.com/nsn/5306-01-164-1123>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.885 inches and 1.925 inches

Fastener Length:

Between 4.020 inches and 4.040 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 1.256 inches and 1.276 inches

Width Between Flats:

1.4375 inches

Extended Washer Diameter:

Between 2.303 inches and 2.313 inches

Extended Washer Thickness:

Between 0.249 inches and 0.279 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

Between 1.3725 inches and 1.3740 inches

Thread Diameter:

1.375 inches

Grip Length:

Between 2.115 inches and 2.135 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches threads

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0