## NSN 5306-01-164-1123

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-164-1123



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 1.885 inches and 1.925 inches Fastener Length: Between 4.020 inches and 4.040 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 1.256 inches and 1.276 inches Width Between Flats: 1.4375 inches **Extended Washer Diameter:** Between 2.303 inches and 2.313 inches **Extended Washer Thickness:** Between 0.249 inches and 0.279 inches Hole Diameter: Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 1.3725 inches and 1.3740 inches **Thread Diameter:** 1.375 inches Grip Length: Between 2.115 inches and 2.135 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 12 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

## NSN 5306-01-164-1123

Shear Bolt - Page 2 of 2



Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A003b0