

View Online at <https://aerobasegroup.com/nsn/5306-01-164-4458>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.371 inches and 0.411 inches

**Fastener Length:**

Between 1.756 inches and 1.776 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.210 inches

**Width Between Flats:**

Between 0.578 inches and 0.585 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.365 inches and 1.385 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.638 inches first hole and 1.668 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0