

View Online at <https://aerobasegroup.com/nsn/5306-01-164-4460>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.433 inches and 0.473 inches

Fastener Length:

Between 2.005 inches and 2.025 inches

Head Style:

Spline drive shear head

Head Height:

Between 0.247 inches and 0.267 inches

Width Between Flats:

Between 0.711 inches and 0.717 inches

Grip Diameter:

Between 0.4365 inches and 0.4370 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Thread Diameter:

0.437 inches

Grip Length:

Between 1.552 inches and 1.572 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.880 inches first hole and 1.910 inches first hole

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0