# NSN 5306-01-164-5835

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-164-5835



## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.456 inches and 0.749 inches

#### Fastener Length:

Between 3.911 inches and 3.931 inches

#### **Head Style:**

Dished hexagon

#### Head Height:

Between 0.313 inches and 0.328 inches

#### Width Between Flats:

Between 0.928 inches and 0.940 inches

#### Grip Diameter:

Between 0.6232 inches and 0.6241 inches

#### **Thread Diameter:**

0.625 inches

## Grip Length:

Between 3.062 inches and 3.078 inches

#### Thready Qty Per Inch (tpi):

18

#### Min. Tensile Strength (psi):

9500 pounds per square inch

#### Hardness Rating:

36.0 rockwell c and 41.0 rockwell c

#### Surface Finish:

63.0 microinches grip

#### Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# **NSN 5306-01-164-5835** Machine Bolt - Page 2 of 2

Fiig: A003b0

