## NSN 5306-01-164-7459

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-164-7459

Thread Class:							
3a							
Thread Direction:							
Right-hand							
Thread Length:							
Between 0.475 inches and 0.525 inches							
Fastener Length:							
Between 0.860 inches and 0.890 inches							
Head Style:							
Double hexagon w/hole							
Head Height:							
Between 0.244 inches and 0.264 inches							
Width Between Flats:							
Between 0.305 inches and 0.313 inches							
Extended Washer Diameter:							
Between 0.465 inches and 0.475 inches							
Extended Washer Thickness:							
Between 0.032 inches and 0.052 inches							
Grip Diameter:							
Between 0.2490 inches and 0.2495 inches							
Thread Diameter:							
0.250 inches							
Grip Length:							
Between 0.365 inches and 0.385 inches							
Thready Qty Per Inch (tpi):							
28							
Min. Tensile Strength (psi):							
200000 pounds per square inch							
Surface Finish:							
32.0 microinches threads							
Material:							
Iron alloy 660							
Material Specification:							
Ams 5737 assn standard single material response							
Surface Treatment:							
Passivate							
Surface Treatment Specification:							
Qq-p-35 federal specification single treatment response							
Thread Series Designator:							
Unif							
Shelf Life:							
N/a							

N/a

## NSN 5306-01-164-7459

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0