NSN 5306-01-164-8515

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-164-8515 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.311 inches and 0.378 inches **Fastener Length:** Between 3.478 inches and 3.498 inches **Head Style:** Dished hexagon **Head Height:** Between 0.157 inches and 0.172 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Grip Diameter:** Between 0.3108 inches and 0.3117 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Thread Diameter:** 0.312 inches **Grip Length:** Between 3.000 inches and 3.016 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 36.0 rockwell c and 41.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 3.363 inches first hole and 3.393 inches first hole **Surface Finish:** 63.0 microinches grip **Special Features:** Retaining element on shank Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 4130 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response

Unjf

Shelf Life:

Thread Series Designator:

N/a

NSN 5306-01-164-8515

Close Tolerance Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0