## NSN 5306-01-165-2439

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-165-2439

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.827 inches and 0.877 inches **Fastener Length:** Between 1.525 inches and 1.555 inches **Head Style:** Spline extended washer **Head Height:** Between 0.358 inches and 0.398 inches **Extended Washer Diameter:** Between 0.922 inches and 0.932 inches **Extended Washer Thickness:** Between 0.062 inches and 0.082 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Head Minor Diameter:** Between 0.644 inches and 0.651 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 2, cl 2 military specification single treatment response **Thread Series Designator:** 

Unf

## NSN 5306-01-165-2439

Shear Bolt - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: