# NSN 5306-01-165-2890

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-165-2890

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

0.283 inches

#### Fastener Length:

0.375 inches

#### Head Style:

Double hexagon w/hole

#### **Head Height:**

0.258 inches

#### Width Between Flats:

0.250 inches

#### Extended Washer Diameter:

# 0.375 inches

### **Extended Washer Thickness:**

0.040 inches

## Hole Diameter:

Between 0.042 inches and 0.052 inches

## **Thread Diameter:**

0.190 inches

# Grip Length:

Between 0.072 inches and 0.092 inches

### Hole Quantity:

4

## Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

1250000 pounds per square inch

### Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

### Hole Configuration Style:

Double hexagon longitudinal hole

#### Material:

Steel comp 8740

## Material Specification:

Ams 6322 assn standard single material response

# Surface Treatment:

Cadmium

# NSN 5306-01-165-2890

Machine Bolt - Page 2 of 2



Surface Treatment Specification:

Ams2400 assn standard single treatment response

## **Thread Series Designator:**

Unjf

Specification Data:

96906-ms9923-04 government standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0