NSN 5306-01-165-3264



Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-165-3264 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.632 inches **Fastener Length:** Between 2.218 inches and 2.250 inches **Head Style:** Hexagon **Head Height:** Between 0.390 inches and 0.422 inches Width Between Flats: Between 1.052 inches and 1.064 inches **Shoulder Diameter:** 0.7485 inches first shoulder and 0.7490 inches first shoulder **Shoulder Length:** 1.586 inches first shoulder and 1.618 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.141 inches first hole and 0.151 inches first hole **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 1.978 inches first hole and 2.010 inches first hole **Shoulder Shape:** Round first shoulder Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5306-01-165-3264

Shoulder Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0