

View Online at <https://aerobasegroup.com/nsn/5306-01-165-3313>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.699 inches and 0.766 inches

**Fastener Length:**

Between 3.459 inches and 3.506 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.328 inches

**Width Between Flats:**

Between 0.904 inches and 0.912 inches

**Grip Diameter:**

Between 0.5610 inches and 0.5615 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.146 inches first hole

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 2.740 inches and 2.760 inches

**Thready Qty Per Inch (tpi):**

18

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.330 inches first hole and 3.387 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0