

View Online at <https://aerobasegroup.com/nsn/5306-01-165-5592>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.355 inches and 0.395 inches

**Fastener Length:**

Between 4.365 inches and 4.385 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.187 inches

**Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.081 inches first hole

**Head Minor Diameter:**

Between 0.415 inches and 0.521 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 3.990 inches and 4.010 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.257 inches first hole and 4.267 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0