NSN 5306-01-165-7533

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-165-7533



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.680 inches and 0.730 inches Fastener Length: Between 2.565 inches and 2.595 inches **Head Style:** Spline extended washer **Head Height:** Between 0.383 inches and 0.403 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** Between 0.053 inches and 0.073 inches Hole Diameter: Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches Head Minor Diameter: Between 0.514 inches and 0.521 inches **Thread Diameter:** 0.438 inches Grip Length: Between 1.865 inches and 1.885 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Passivate

NSN 5306-01-165-7533

Shear Bolt - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0