

View Online at <https://aerobasegroup.com/nsn/5306-01-166-4539>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.750 inches

**Fastener Length:**

2.070 inches

**Head Style:**

Hexagon

**Head Height:**

0.140 inches

**Width Between Flats:**

0.491 inches

**First Diameter From Head:**

Between 0.246 inches and 0.249 inches

**Second Diameter From Head:**

Between 0.190 inches and 0.195 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.180 inches and 0.210 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 1.956 inches and 2.016 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Externally Relieved Body Diameter Quantity:**

2

**Special Features:**

Second diameter from head rounded both sides 0.195 in. From full diameter of 0.250 in.

**Material:**

Steel

**Material Specification:**

Hr 650, fscm k0378 mfr ref single material response

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Dtd 939, fscm k0378 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0