NSN 5306-01-166-6899

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-166-6899 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.763 inches and 0.813 inches **Fastener Length:** Between 4.398 inches and 4.428 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.504 inches Width Between Flats: 0.562 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** 0.123 inches **Grip Diameter:** Between 0.5007 inches and 0.5019 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 3.615 inches and 3.635 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

٠.

Shelf Life:

N/a

NSN 5306-01-166-6899

Shear Bolt - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0