## NSN 5306-01-166-6900

Shear Bolt - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5306-01-166-6900

| 3a  |
|---|
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.763 inches and 0.813 inches                                     |
| Fastener Length:  |
| Between 4.398 inches and 4.428 inches                                     |
| Head Style:   |
| Double hexagon w/hole   |
| Head Height:  |
| 0.504 inches  |
| Width Between Flats:  |
| 0.562 inches  |
| Extended Washer Diameter:   |
| Between 0.818 inches and 0.828 inches                                     |
| Extended Washer Thickness:  |
| 0.123 inches  |
| Grip Diameter:  |
| Between 0.5107 inches and 0.5119 inches                                   |
| Thread Diameter:  |
| 0.500 inches  |
| Grip Length:  |
| Between 3.615 inches and 3.635 inches                                     |
| Thready Qty Per Inch (tpi):   |
| 20  |
| Min. Tensile Strength (psi):  |
| 180000 pounds per square inch   |
| Hardness Rating:  |
| 39.0 rockwell c and 43.0 rockwell c                                       |
| Surface Finish:   |
| 32.0 microinches grip   |
| Product Name:   |
| Navy special project  |
| Material:   |
| Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150 |
| Surface Treatment:  |
| Cadmium and chromate  |
| Surface Treatment Specification:  |
| Qq-p-416, type 2, cl 2 federal specification single treatment response    |
| Thread Series Designator:   |
| Unif  |

## NSN 5306-01-166-6900

Shear Bolt - Page 2 of 2



| -  |    |     |      |  |
|----|----|-----|------|--|
| ٠. | hΔ | Iŧ. | ife: |  |
|    |    |     |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0