## NSN 5306-01-167-1086

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-167-1086
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.148 inches and 1.198 inches
Fastener Length:
Between 3.408 inches and 3.438 inches
Head Style:
Spline extended washer
Head Height:
0.492 inches
Extended Washer Diameter:
Between 1.384 inches and 1.394 inches
Extended Washer Thickness:
Between 0.083 inches and 0.112 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
Head Minor Diameter:
Between 0.797 inches and 0.812 inches
Thread Diameter:
0.750 inches
Grip Length:
Between 2.240 inches and 2.260 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837, ty2 cl2 military specification single treatment response
Thread Series Designator:

Unjf

## NSN 5306-01-167-1086

Shear Bolt - Page 2 of 2



Shelf	Life:
N/a	

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.