

View Online at <https://aerobasegroup.com/nsn/5306-01-167-4349>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.560 inches and 0.643 inches

Fastener Length:

Between 1.445 inches and 1.465 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.378 inches and 0.398 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

Between 0.081 inches and 0.101 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

0.812 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas1785 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0