

View Online at <https://aerobasegroup.com/nsn/5306-01-169-7233>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.886 inches and 0.953 inches

**Fastener Length:**

Between 2.334 inches and 2.381 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.350 inches

**Width Between Flats:**

Between 0.970 inches and 0.978 inches

**Hole Diameter:**

Between 0.065 inches and 0.074 inches

**Grip Diameter:**

Between 0.6235 inches and 0.6240 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.146 inches first hole

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 1.428 inches and 1.448 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

145000 pounds per square inch

**Hole Configuration Style:**

Spline

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.080 inches first hole and 2.137 inches first hole

**Material:**

Cobalt comp mp-35-n

**Material Specification:**

Ams 5844 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0