NSN 5306-01-169-7592

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-169-7592

| 3a |
|---|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.579 inches |
| Fastener Length: |
| 3.599 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| 0.348 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Extended Washer Diameter: |
| Between 0.521 inches and 0.531 inches |
| Extended Washer Thickness: |
| 0.082 inches |
| Grip Diameter: |
| Between 0.3110 inches and 0.3120 inches |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 3.589 inches and 3.609 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 39.0 rockwell c and 43.0 rockwell c |
| Material: |
| Steel comp 4140 |
| Surface Treatment: |
| Cadmium |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 96906-ms21250-05048 government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5306-01-169-7592

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0