## NSN 5306-01-170-3456

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-170-3456 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.330 inches and 0.360 inches **Fastener Length:** Between 1.142 inches and 1.172 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A003b0

## NSN 5306-01-170-3456

Shear Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.