NSN 5306-01-170-3460

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-170-3460 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.410 inches and 0.440 inches **Fastener Length:** Between 2.660 inches and 2.690 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 2.240 inches and 2.280 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, ty2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A003b0

NSN 5306-01-170-3460

Shear Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.