

View Online at <https://aerobasegroup.com/nsn/5306-01-170-4568>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.886 inches and 0.953 inches

Fastener Length:

Between 1.708 inches and 1.755 inches

Head Style:

Spline drive shear head

Head Height:

0.350 inches

Width Between Flats:

Between 0.970 inches and 0.978 inches

Hole Diameter:

Between 0.065 inches and 0.074 inches

Grip Diameter:

Between 0.6235 inches and 0.6240 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.146 inches first hole

Thread Diameter:

0.625 inches

Grip Length:

Between 0.802 inches and 0.822 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

145000 pounds per square inch

Hole Configuration Style:

Spline

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.454 inches first hole and 1.511 inches first hole

Material:

Cobalt comp mp-35-n

Material Specification:

Ams 5844 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0