NSN 5306-01-171-3414

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-171-3414

View Offiline at https://defobasegroup.com/hsh/5500-01-171-5414
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.400 inches and 0.450 inches
Fastener Length:
Between 0.722 inches and 0.752 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6704 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-01-171-3414

Shear Bolt - Page 2 of 2



em			

No

Fiig:

A003b0