

View Online at <https://aerobasegroup.com/nsn/5306-01-171-6504>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.661 inches and 0.711 inches

Fastener Length:

Between 3.796 inches and 3.826 inches

Head Style:

Spline extended washer

Head Height:

Between 0.231 inches and 0.271 inches

Width Between Flats:

Between 0.383 inches and 0.389 inches

Extended Washer Diameter:

Between 0.521 inches and 0.531 inches

Extended Washer Thickness:

Between 0.051 inches and 0.071 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 3.115 inches and 3.135 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Chromium and chromate

Surface Treatment Specification:

Mil-c-8837, type 2, class 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.