## NSN 5306-01-171-6504

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-171-6504

View Online at https://aerobasegroup.com/nsn/5306-01-171-6504
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.661 inches and 0.711 inches
Fastener Length:
Between 3.796 inches and 3.826 inches
Head Style:
Spline extended washer
Head Height:
Between 0.231 inches and 0.271 inches
Width Between Flats:
Between 0.383 inches and 0.389 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
Between 0.051 inches and 0.071 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 3.115 inches and 3.135 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Material:
Steel comp h11
Material Specification:
Ams6487 assn standard single material response
Surface Treatment:
Chromium and chromate
Surface Treatment Specification:
Mil-c-8837, type 2, class 2 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N1/-

N/a

## NSN 5306-01-171-6504

Shear Bolt - Page 2 of 2



		. ~				
ı	ını	t Of	· M	മമ	CII	re.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.