NSN 5306-01-172-2541

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-172-2541
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.298 inches and 0.348 inches
Fastener Length:
Between 3.995 inches and 4.025 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 3.677 inches and 3.697 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6203 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5306-01-172-2541

Shear Bolt - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.