

View Online at <https://aerobasegroup.com/nsn/5306-01-172-5538>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.607 inches and 0.657 inches

**Fastener Length:**

Between 0.679 inches and 0.709 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.172 inches and 0.204 inches

**Width Between Flats:**

Between 0.492 inches and 0.501 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.052 inches and 0.072 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.411 inches first hole and 0.431 inches first hole

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response or ams 5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1005 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0