

View Online at <https://aerobasegroup.com/nsn/5306-01-173-6778>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.874 inches and 1.062 inches

**Fastener Length:**

Between 1.688 inches and 1.750 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.195 inches and 0.211 inches

**Width Between Flats:**

Between 0.489 inches and 0.500 inches

**Shank Unthreaded Hole Diameter:**

0.074 inches first hole and 0.082 inches first hole

**End Application:**

Spec item

**Thread Diameter:**

0.312 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.553 inches first hole and 1.635 inches first hole

**Material:**

Steel

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Mil-p-16232 ty z, cl 2 military specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

2 type and 10p style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-p-16232 spec.