

View Online at <https://aerobasegroup.com/nsn/5306-01-173-7816>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.282 inches and 0.499 inches

Fastener Length:

Between 2.719 inches and 2.812 inches

Head Style:

Hexagon

Head Height:

Between 0.172 inches and 0.204 inches

Width Between Flats:

Between 0.365 inches and 0.377 inches

Hole Diameter:

0.046 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole

Thread Diameter:

0.190 inches

Grip Length:

Between 2.313 inches and 2.437 inches

Hole Quantity:

1

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Hole Configuration Style:

Hexagon flats

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.578 inches first hole and 2.703 inches first hole

Material:

Steel comp 321 or steel comp 347

Material Specification:

Qq-s-763 federal specification all material responses or ams 5645 assn standard 1st material response or ams 5646 assn standard 2nd material response

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Specification Data:

80205-nas501 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0