

View Online at <https://aerobasegroup.com/nsn/5306-01-174-0529>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.355 inches and 0.395 inches

**Fastener Length:**

Between 1.865 inches and 1.885 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.187 inches

**Width Between Flats:**

Between 0.514 inches and 0.521 inches

**Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.081 inches first hole

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 1.490 inches and 1.510 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.747 inches first hole and 1.777 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0