

View Online at <https://aerobasegroup.com/nsn/5306-01-175-0990>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.190 inches and 1.500 inches

**Fastener Length:**

Between 1.440 inches and 1.500 inches

**Head Style:**

Distorted head

**Head Height:**

Between 0.312 inches and 0.327 inches

**Width Between Flats:**

Between 0.736 inches and 0.750 inches

**Locking Feature:**

Distortions bearing surface of head

**Thread Diameter:**

0.500 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Material:**

Steel

**Material Specification:**

Sae gr8 assn standard all material responses

**Surface Treatment:**

Phosphate zinc

**Surface Treatment Specification:**

Mil-p-16232, type z, class 2 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-p-16232 spec.