## NSN 5306-01-175-2116



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-175-2116 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.651 inches and 0.766 inches **Fastener Length:** Between 0.734 inches and 0.766 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.306 inches and 0.312 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.457 inches and 0.468 inches **Extended Washer Thickness:** Between 0.083 inches and 0.103 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Thread Diameter:** 0.312 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 170000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 3 federal specification single treatment response **Thread Series Designator:** 

Unf

Shelf Life:

N/a

## **NSN 5306-01-175-2116**Machine Bolt - Page 2 of 2



	Of			

Demilitarization:

No

Fiig:

A003b0