NSN 5306-01-175-3623

Machine Bolt - Page 1 of 2

Between 0.650 inches and 0.761 inches

Between 0.771 inches and 0.791 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-175-3623

Hexagon Head Height: 0.219 inches Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.250 inches Grip Length: Between 0.030 inches and 0.060 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c
Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.250 inches Grip Length: Between 0.030 inches and 0.060 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Width Between Flats: Between 0.428 inches and 0.440 inches Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.250 inches Grip Length: Between 0.030 inches and 0.060 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Between 0.428 inches and 0.440 inches Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.250 inches Grip Length: Between 0.030 inches and 0.060 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.250 inches Grip Length: Between 0.030 inches and 0.060 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Between 0.070 inches and 0.080 inches Thread Diameter: 0.250 inches Grip Length: Between 0.030 inches and 0.060 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Thread Diameter: 0.250 inches Grip Length: Between 0.030 inches and 0.060 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
0.250 inches Grip Length: Between 0.030 inches and 0.060 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Grip Length: Between 0.030 inches and 0.060 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Between 0.030 inches and 0.060 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
160000 pounds per square inch Hardness Rating:
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon corners
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

NSN 5306-01-175-3623 Machine Bolt - Page 2 of 2

Fiig: A003b0



Thread Series Designator:
Unjf
Specification Data:
80205-nas564 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No