NSN 5306-01-175-3641

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-175-3641 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.538 inches and 0.641 inches **Fastener Length:** Between 0.609 inches and 0.641 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.244 inches and 0.250 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.365 inches and 0.375 inches **Extended Washer Thickness:** Between 0.052 inches and 0.072 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Thread Diameter:** 0.250 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:**

Unf

Shelf Life:

N/a

NSN 5306-01-175-3641Machine Bolt - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

Demilitarization:

No

Fiig:

A003b0