NSN 5306-01-175-5355

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-175-5355

View Online at https://aerobasegroup.com/nsn/5306-01-175-5355							
Thread Class:							
2a							
Thread Direction:							
Right-hand							
Thread Length:							
Between 1.000 inches and 1.188 inches							
Fastener Length:							
Between 4.156 inches and 4.250 inches							
Head Style:							
Hexagon							
Head Height:							
Between 0.226 inches and 0.243 inches							
Width Between Flats:							
Between 0.5510 inches and 0.5625 inches							
Hole Diameter:							
Between 0.0605 inches and 0.0685 inches							
Locking Feature:							
Patch threads							
Thread Diameter:							
0.375 inches							
Hole Quantity:							
Hole Quantity: 1							
1							
1 Hole Type:							
1 Hole Type: Drilled							
1 Hole Type: Drilled Features Provided:							
1 Hole Type: Drilled Features Provided: Finished head							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi):							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi):							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi):							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 150000 pounds per square inch							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating:							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style:							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon flats							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon flats Material:							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel Surface Treatment:							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel Surface Treatment: Cadmium and chromate							
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification:							

NSN 5306-01-175-5355

Machine Bolt - Page 2 of 2



c	peci	ficat	ion	Or	C+2	nd	ard	ı
3	Deci	ncat	ion	Ul.	Sta	na	aru	ı.

2 type and 10p style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0