NSN 5306-01-175-5356

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-175-5356

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 1.500 inches and 1.727 inches
Fastener Length:
Between 2.156 inches and 2.250 inches
Head Style:
Hexagon
Head Height:
Between 0.378 inches and 0.403 inches
Width Between Flats:
Between 0.9220 inches and 0.9375 inches
Hole Diameter:
Between 0.092 inches and 0.100 inches
Locking Feature:
Patch threads
Thread Diameter:
Thread Diameter: 0.625 inches
0.625 inches
0.625 inches Hole Quantity:
0.625 inches Hole Quantity:
0.625 inches Hole Quantity: 1 Hole Type:
0.625 inches Hole Quantity: 1 Hole Type: Drilled
0.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided:
0.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head
0.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi):
0.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi):
0.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi):
0.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 150000 pounds per square inch
0.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating:
0.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener
0.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Hole Configuration Style:
0.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Hole Configuration Style: Hexagon flats
0.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Hole Configuration Style: Hexagon flats Special Features:
O.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Hole Configuration Style: Hexagon flats Special Features: Locking feature is plastic polyamide
O.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Hole Configuration Style: Hexagon flats Special Features: Locking feature is plastic polyamide Material:
O.625 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Hole Configuration Style: Hexagon flats Special Features: Locking feature is plastic polyamide Material: Steel

Zinc fastener and chromate fastener

NSN 5306-01-175-5356

Machine Bolt - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Astm b633 type 2 sc 3 assn standard single treatment response fastener

Thread Series Designator:

Unc

Specification Or Standard:

2 type and 10p style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0