

View Online at <https://aerobasegroup.com/nsn/5306-01-175-6919>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.346 inches and 0.430 inches

**Fastener Length:**

Between 1.160 inches and 1.190 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.156 inches and 0.171 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Shoulder Diameter:**

0.3115 inches first shoulder and 0.3120 inches first shoulder

**Shoulder Length:**

0.740 inches first shoulder and 0.760 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.972 inches first hole and 1.022 inches first hole

**Shoulder Shape:**

Round first shoulder

**Product Name:**

Navy special project

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0